


# Interactive Flat Panel Display

TA-65/TA-75/TA-86



UHD  
Resolution



8GB RAM  
128GB ROM



40 touch  
points



Android 14



Zero bonding



Share screen



USB Type-C



8 arrays



Split screen



Remote control

Interactive Flat Panel Display

<b>Display</b>			
Size	65inch	75inch	86inch
Type	DLED		
Aspect ratio	16:9		
Screen display size (mm)	1428*803	1646*926	1892*1064
Physical resolution	3840 × 2160 (4k)		
Display color	10bit/1.07 Billion		
Refresh rate	60Hz		
Brightness	≥400cd/m <sup>2</sup>		
Contrast	4000:1		
Response time	6ms		
Viewing angle	178°/ 178°		
Display protection	4mm full tempered high explosion-proof glass		
Backlight life	50000 hours		
<b>System</b>			
CPU	8*A55		
System version	Android 14		
RAM	8GB		
ROM	128GB		
Operating temperature	0°C-40°C		
<b>INTERACTIVITY</b>			
Touch Technology	IR		
Touch points	40 points		
Positioning Accuracy	1mm		
Drive Mode	Drive Mode		
Writing method	Fingers, touch pens or other non-transparent objects not less than 5mm in diameter		
Palm erase	Yes		
Communication Port	USB 3.0		
Reaction time (Single touch)	<4ms		
Touch resolution	32768 x 32768		
Times of touches	Unlimited time in theoretical		
Transfer speed	12Mb/s		

## Interactive Flat Panel Display

Compatibility	Support windows, Android, Mac OS, Linux		
<b>Connectivity</b>			
<b>Back port</b>			
HDMI IN	X1		
HDMI OUT	x1		
VGA	X1		
Audio	X1		
Coax	X1		
Earphone	X1		
Mic	X1		
TF CARD	X1		
USB 3.0	X1		
USB 2.0	X1		
TOUCH OUT	X1		
LAN	X1		
WIFI	Wifi 6, support 100Mbps		
OPS slot	X1		
<b>Front port</b>			
HDMI IN	X1		
USB-A 3.0	X3		
USB TOUCH	x1		
USB-C	x1		
<b>Dimension</b>			
Overall dimensions (mm, LxWxT)	1485*105*905	1708*105*1027	1954*105*1165
Net weight	37.7kg	51.5kg	67.2kg
Gross weight	46.5kg	64.6kg	85.2kg
Packaging size (mm, LxWxT)	1600*205*1002	1846*215*1180	2092*215*1319
VESA	500x400	600x400	800x400
<b>Power Supply</b>			
Consumption rate	≤190W	≤270W	≤320W
Standby power	≤1W		

## Interactive Flat Panel Display

Voltage range	AC100-240V~50/60Hz
Speaker specification	2 x 15 Watts
Operating temperature	32°F-104°F (0°C-40°C)
Storage temperature	-4°F -140°F (-20°C-60°C)
Humidity	5%-80% relative humidity, non-condensing

## Built-camera and mic parameter

Microphones	8 integrated microphones
Pickup distance	10m
Sample rate	Sampling frequency 48K Hz; sampling number 24bit
Features	Full duplex, echo cancellation, noise suppression
Camera resolution	Support 1080P
Camera	48 Megapixels, top x 1
Camera lens angle	120°

## Accessories

Power cable	x1
Remote control	x1
Wall mount	x1
HDMI & Touch USB cable	x1
Whiteboard pen	x2



SINOVIEW TECHNOLOGY CO., LTD

[www.sinoeview.com](http://www.sinoeview.com)

1004-1005, Building C, Longhua Digital Innovation Center, Shenzhen, China

[market@tacteas.com](mailto:market@tacteas.com)